

09/11/00
JCS949 U.S. PTO

10-13 00

F

Please type a plus sign (+) inside this box ☒
 Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Approved for use through 10/31/2002. OMB 0861-0002
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. STGUP006
First Inventor Stefan LUNDBERG
Title
Express Mail Label No. EK802176656US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☐ Applicant claim main title status.
See 37 CFR 1.127.
3. ☒ Specification [Total Pages 18]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 6] Page 1-7
5. Oath or Declaration [Total Pages 18]
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63 (d))
(for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(e).
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Form (CRF)
 - b. Specification Sequence Listing on:
 - i. ☐ CD-ROM or CD-R (2 copies); or
 - ii. ☐ paper
 - c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement of Power of Attorney (when there is an assignee)
11. ☐ English Translation Document (if applicable)
12. ☒ Information Disclosure Statement (IDS)/PTO-1449 ☒ Copies of IDS Citations
13. ☒ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☒ Other: unsigned Combined Declaration and Power of Attorney.....

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:
☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____
Prior application information Examiner _____ Group / Art Unit _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Form 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label ☒ Correspondence address below

Name CARY & KELLY, LLP
ATTN: Charles C. Cary
Address 1875 Charleston Road
City Mountain View State California Zip Code 94043
Country United States Telephone (650) 316-4011 Fax (650) 316-4013

Name (Print/Type)	Charles C. Cary	Registration No. (Attorney/Agent)	36,764
Signature		Date	Oct 11, 2000

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

09669181.101106

PTO/SB/05 (08-00)
08-181699/60
09/11/00

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$) 1,050

Complete if Known

Application Number	n/a
Filing Date	Oct 11, 2000
First Named Inventor	Stefan LUNDBERG
Examiner Name	N/A
Group Art Unit	N/A
Attorney Docket No.	STGUP006

METHOD OF PAYMENT

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

Deposit Account Number: 50-1338
Deposit Account Name: CARY & KELLY, LLP

- ☒ Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17

☐ Applicant claims small entity status. See 37 CFR 1.27

2. ☒ Payment Enclosed:

☒ Check ☐ Credit card ☐ Money Order ☐ Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity	Small Entity	Fee Code	Fee Code	Fee Description	Fee Paid
101	710	201	355	Utility filing fee	\$710
106	320	206	160	Design filing fee	
107	490	207	245	Plant filing fee	
108	710	208	355	Reissue filing fee	
114	150	214	75	Provisional filing fee	

SUBTOTAL (1) (\$) 710

2. EXTRA CLAIM FEES

Total Claims	Extra Claims	Fee from below	Fee Paid
30	-20 = 10	X \$18 =	\$180
5	-3 = 2	X 80 =	\$160
Multiple Dependent			\$0

Large Entity Small Entity

Fee Code	Fee Code	Fee Description
103	18 203 9	Claims in excess of 20
102	80 202 40	Independent claims in excess of 3
104	270 204 135	Multiple dependent claim, if not paid
109	80 209 40	** Reissue independent claims over original patent
110	18 210 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$) 340

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity	Small Entity	Fee Code	Fee Code	Fee Description	Fee Paid
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for <i>ex parte</i> reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension for reply within first month	
116	390	216	195	Extension for reply within second month	
117	800	217	445	Extension for reply within third month	
118	1,390	218	695	Extension for reply within fourth month	
128	1,890	228	945	Extension for reply within fifth month	
119	310	219	155	Notice of Appeal	
120	310	220	155	Filing a brief in support of an appeal	
121	270	221	135	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,240	241	620	Petition to revive - unintentional	
142	1,240	242	620	Utility issue fee (or reissue)	
143	440	243	220	Design issue fee	
144	600	244	300	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	
146	710	246	355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	710	249	355	For each additional invention to be examined (37 CFR § 1.129(b))	
179	710	279	355	Request for Continued Examination (RCE)	
169	900	169	900	Request for extended examination of a design application	

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) _____

SUBMITTED BY

Name (Print/Type)	Charles C. Cary	Registration No. (Attorney/Agent)	36,764	Complete (if applicable)	
Signature		Date	Oct 11, 2000	Telephone	(650) 316-4011

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

CERTIFICATE OF EXPRESS MAILING

I hereby certify that this paper and the documents and/or fees referred to as attached therein are being deposited with the United States Postal Service on October 11, 2000 in an envelope as "Express Mail Post Office to Addressee" service under 37 CFR 510.6. Mailing Label Number EK802176656US, addressed to the Assistant Commissioner for Patents, Washington, DC 20231.

Date: October 11, 2000

Signed: _____

Charles C. Cary

Patent

Attorney's Docket No. [STGUP006]

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of)
Stefan LUNDBERG.) Group Art Unit: n/a
Application No.: n/a) Examiner: n/a
Filed: Herewith)
For: AN IMAGE ALTERING DEVICE)
FOR AN IMAGE PRODUCING)
APPARATUS)

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Before examination, please amend this application as follows.

IN THE SPECIFICATION:

After the title please add the following paragraph:

-- RELATED APPLICATION

This application claims priority of prior filed Swedish Application No. 0002554-4 by inventor Stefan Lundberg entitled "An Image Altering Device for an Image Producing Apparatus" filed on July 7, 2000 which is hereby incorporated by reference. --

IN THE CLAIMS:

Please Amend Claims 1-23 as follows, and add new Claims 24-30.

1. (Amended) An image altering device for an image producing apparatus [(300)] with an

optical input [(5)] characterized by:

a mirror [(1)] having a first plane surface [(2)] and a second curved surface [(3)]

a driving device [(7)] coupled to the mirror [(1)] and adapted to rotate the mirror [(1)] to a first position, where the first plane surface [(2)] is inserted into an optical path [(31)] of the image producing apparatus (6), the optical path being external to the optical input [(5)], thereby providing a first field of view of the image producing apparatus, the driving device [(7)] also being adapted to rotate the mirror [(1)] to a second position, where the second curved surface [(3)] is inserted into the optical path of the image producing apparatus, thereby providing a second field of view of the image producing apparatus.

2. (Amended) A device according to claim 1, where the curved surface [(3)] forms a portion of a sphere.
3. (Amended) A device according to claim 1 [or 2], where the first plane surface [(2)] has an angular displacement of 180 degrees with respect to the second curved surface [(3)].
4. (Amended) A device according to [any of] claims 1[-3], where the mirror [(10)] comprises a third surface [(13)] with an optical characteristic different from the first plane surface [(11)] or the second curved surface [(12)] the driving device [(17)] being adapted to rotate the mirror [(10)] to a third position, where the third surface [(13)] is inserted into the optical path of the image producing apparatus.
5. (Amended) A device according to claim 4, where the third surface [(13)] is plane.
6. (Amended) A device according to claim 4 [or 5], where the third surface [(13)] attenuates certain spectral components of the reflected light.
7. (Amended) A device according to claim 6, where the spectral components of the reflected light are uniformly attenuated.
8. (Amended) A device according to [any preceding] claim 1, where the driving device [(7)]

is adapted to receive a control signal from a control unit [(600)] and to rotate the mirror [(1)] to the first position or to the second position depending on a value of the control signal.

9. (Amended) A device according to [any preceding] claim 1, where the driving device [(7)] comprises at least one belt for rotating the mirror.

10. (Amended) A device according to [any preceding] claim 1, where the driving device [(7)] comprises at least one gear wheel for rotating the mirror.

11. (Amended) A method of providing a plurality of fields of view of an image producing apparatus, characterized by:

rotating a mirror [(1)] having a first plane surface [(2)] to a first position, where the first surface [(2)] is inserted into an optical path [(31)] of the image producing apparatus, thereby providing a first field of view, the optical path being external to the optical input, and

rotating the mirror [(1)] to a second position, where a second curved surface [(3)] is inserted into the optical path of the image producing apparatus, thereby providing a second field of view of the image producing apparatus.

12. (Amended) A method according to claim 11, where the mirror [(1)] is rotated by an angle of 180 degrees.

13. (Amended) A method according to claim 11 [or 12], where the mirror [(10)] comprises a third surface [(13)] with an optical characteristic different from the first plane surface [(11)] or the second curved surface [(12)], the third surface [(13)] being inserted into the optical path of the image producing apparatus, thereby providing a third field of view of the image producing apparatus.

14. (Amended) A digital camera [(300)] having panning and/ or tilting functionality, comprising: a camera housing [(6)] with an optical input [(5)], such as a lens or objective; an image capturing unit [(500)] for producing a digital image from light received through the

optical input [(5)]; and a controller [(600)], **characterized** by:

a mirror [(1)] , mounted externally to the camera 25 housing [(6)], having a first plane surface [(2)] and a second curved surface [(3)] , and

a driving device [(7)] coupled to the mirror [(1)] and adapted to rotate the mirror [(1)] to a first position, where the first plane surface [(2)] is inserted into an optical path [(31)] of the digital camera [(300)], the optical path being external to the optical input [(5)], thereby providing a first field of view of the digital camera, the driving device [(7)] also being adapted to rotate the mirror [(1)] to a second position, where the second curved surface [(3)] is inserted into the optical path of the digital camera, thereby providing a second field of view of the digital camera.

15. (Amended) A digital camera according to claim 14, where the curved surface [(3)] forms a portion of a sphere.

16. (Amended) A digital camera according to claim 14 [or 15], where the first plane surface [(2)] has an angular displacement of 180 degrees with respect to the second curved surface [(3)].

17. (Amended) A digital camera according to [any of claims] claim 14[-16], where the mirror [(10)] comprises a third surface [(13)] with an optical characteristic different from the first plane surface [(11)] or the second curved surface [(12)], the driving device [(17)] being adapted to rotate the mirror [(10)] to a third position, where the third surface [(13)] is inserted into the optical path of the digital camera.

18. (Amended) A digital camera according to claim 17, where the third surface [(13)] is plane.

19. (Amended) A digital camera according to claim 17 [or 18], where the third surface [(13)] attenuates certain spectral components of the reflected light.

20. (Amended) A digital camera according to claim 19, where the spectral components of the reflected light are uniformly attenuated.

21. (Amended) A digital camera according to [any of claims] claim 14[-20], where the driving device [(7)] is adapted to receive a control signal from a control unit and to rotate the mirror [(1)] to the first position or to the second position depending on a value of the control signal.

22. (Amended) A device according to [any of claims] claim 14[-21], where the driving device [(7)] comprises at least one belt for rotating the mirror.

23. (Amended) A device according to [any of claims] claim 14[-22], where the driving device [(7)] comprises at least one gear wheel for rotating the mirror.

24. (New) An imaging system for providing an image along an optical axis of an input of an image producing apparatus, and the imaging system comprising:

a first reflector positioned to intersect the optical axis at an angle and the first reflector rotatable about the optical axis; and

a second reflector optically coupled with said first reflector and said second reflector radially displaced from said first reflector about the optical axis and said second reflector configured both for rotation about the optical axis and for tilting with respect to the optical axis to alter an image provided to the input of the image producing apparatus.

25. (New) The imaging system of Claim 24, further comprising:

a planetary linkage of said first reflector and said second reflector including:

a) a guide wheel rotatable about the optical axis, and said first reflector affixed to said guide wheel and said second reflector tiltably affixed to said guide wheel both for rotation about said optical axis;

b) a mirror wheel rotatable about the optical axis; and

c) a planetary member mechanically coupled to both said guide wheel and said mirror wheel such that a relative rotation there between produces a rotation of said planetary member and said planetary member further coupled to said second reflector such that the rotation of said planetary member effects the tilting of said second reflector.

26. (New) The imaging system of Claim 24, wherein said second reflector further comprises:
at least a first reflective surface and a second reflective surface each alternately optically coupled with said first reflector in response to the tilting of said second reflector and each providing a distinctive field of view.
27. (New) A method for providing an image along an optical axis of an input of an image producing apparatus, and the method for providing comprising the acts of:
positioning a first reflector to intersect the optical axis at an angle;
positioning a second reflector along a radius about the optical axis; and
rotating the first reflector together and the second reflector about the optical axis to pan an image provided to the input of the image producing apparatus.
28. (New) The method for providing an image of Claim 27, further comprising the act of:
tilting the second reflector to tilt the image provided to the input of the image producing apparatus.
29. (New) The method for providing an image of Claim 27, further comprising the act of:
providing at least a first reflective surface and a second reflective surface on the second reflector each providing a distinctive magnification from the other; and
tilting the second reflector to vary a magnification level of the view provided to the input of the image producing apparatus.
30. (New) The method for providing an image of Claim 28, further comprising the act of:
providing at least a first reflective surface and a second reflective surface on the second

reflector each providing a distinctive magnification from the other; and
tilting the second reflector to vary a magnification level of the view provided to the input
of the image producing apparatus.

REMARKS

The specification and claims have been amended to place the application in better form
for examination. Favorable consideration is respectfully solicited.

Respectfully submitted,
CARY & KELLY, LLP

Date: October 11, 2000 Signed: _____

Charles C. Cary
Registration No. 36,764

CARY & KELLY, LLP
1875 Charleston Road
Mountain View, California 94043
Telephone: 650.533.4844
Fax: 650.316.4013

09689131 101100

AN IMAGE ALTERING DEVICE FOR AN IMAGE PRODUCING APPARATUS

5 Technical Field

Generally speaking the present invention relates to digital cameras, and more specifically to a digital camera having a camera housing with an optical input, such as a lens or objective, an image capturing unit and a controller. The invention also relates to an image altering device, providing the camera with a panning and/or tilting functionality as well as a functionality for changing the system magnification in fixed steps.

15

Background Art

Camera systems with a wide field of view capability have been in existence for several years. These systems are normally based upon a more or less complex optical system comprising lenses and/or mirrors. In U.S. Pat. No. 5,907,433 to Voigt et. al., a plurality of optical groups are rotatably mounted on a rotary assembly to allow one of the groups to be inserted into the optical path. By using different sets of optical elements a multi-field of view is achieved. One method to obtain panning and/or tilting functionality is described in U.S. Pat. No. 5,717,512 to Chmielewski, Jr. et. al., This invention uses two wide field of view cameras to determine the coordinates of an object, and from that information adjust a rotatable plane pan/tilt mirror to direct light reflected from the object to a narrow field of view camera. Another approach to achieve wide-angle imaging is described in U.S. Pat. No. 5,790,182 to St. Hilaire, where fixed concentric spherical mirrors are used to direct light from an object onto a CCD (Charge Coupled Device) array. By this arrangement the system

is capable of capturing an image spanning a 360 degree field of view. No provision is shown for varying the field of view of the device.

5 **Summary of the Invention**

 An object of the present invention is to provide a digital camera with a variable field of view combined with a tilting and/or panning functionality, being able to cover a greater visual volume than a
10 conventional panning and/or tilting camera. Furthermore, it is an object of the present invention to provide an image steering and magnification/reduction device (referred to as "image altering device" in the following), to be mounted externally on the digital
15 camera, for providing an efficient way of altering the field of view as well as changing the direction of sight. Another object of the present invention is to provide a simple method and apparatus to filter the light reflected from an object.

20 In carrying out the above objects and other objects and features of the present invention, the digital camera is provided with an externally mounted image steering and magnification/reduction device comprising a rotary mirror with at least one side having
25 a curved surface. The tilting mirror is rotated within a minor predefined angle with respect to the optical input of the camera to change the direction of sight and by a major predefined angle to alter the field of view or to insert a filter in the optical path.
30 By using a mirror with a curved surface, for a given field of view, the absolute size and weight of the mirror can be reduced, thereby making it possible to increase the rotary speed of the mirror and thus improving the overall speed of which the direction of
35 sight can be changed from a first to a second position.

00000101-101100

The digital camera also comprises a control unit and an externally mounted driving device for rotating the tilting mirror according to a control signal generated in the control unit.

Brief Description of the Drawings

A preferred embodiment of the present invention will now be described in more detail, reference being made to the accompanying drawings, in which:

FIG 1 is a schematic block diagram of the overall structure of a digital camera and an image altering device according to the preferred embodiment,

FIG 2 is a first side view of the image altering device and the camera, to which it is mounted,

15 FIG 3 is a second side view of the image altering device and the camera shown in FIG 2.

FIG 4 is a top view of the image altering device shown in FIGs 2 and 3.

FIG 5 is a simplified schematic drawing of
20 the main functional parts of the preferred embodiment,
where the tilting mirror is positioned to achieve a
wide field of view.

FIG 6 is a simplified schematic drawing of the main functional parts of the preferred embodiment, where the mirror is positioned to achieve a narrower field of view, and

FIG 7 is a simplified schematic drawing of the main functional parts of a first alternative embodiment.

Detailed Description of the Preferred Embodiments

Referring first to FIG 1, a digital camera 300 is illustrated in a basic modular form. The digital camera 300 is arranged to produce one or several digi-

tal image(s) of a generic object 100, which may be any physical object that is present in a volume optically covered by the digital camera 300. An inventive image altering device 200 is mounted externally to the digital camera 300 in front of an optical input 400 of the digital camera. The optical input 400 is a generally known lens or objective. The purpose of the image altering device 200 is to provide the digital camera 300 with a variable field of view in combination with panning and/or tilting functionality. A preferred embodiment of the image altering device 200 will be described in more detail with reference to FIGs 2-7.

As shown in FIG 1, the digital camera 300 further comprises an image capturing unit 500, which is provided with appropriate means for producing a digital image representative of the object 100. Preferably, the image capturing unit 500 comprises a CCD element (Charge Coupled Device), the internal structure of which is believed to be well-known to a man skilled in the art. The digital camera 300 also has a controller 600 for controlling the image capturing unit 500 as well as the external image altering device 200. The controller 600 is operatively connected not only to the device 200 and the unit 500 but also to a digital memory 700 for storing images captured by the image capturing unit 500. Furthermore, the digital camera 300 may comprise an image transforming unit 800, the purpose of which is to rotate the digital image to compensate for image rotating effects caused by the image altering device 200, when the field of view is panned or tilted. The image transforming unit 800 is responsive to an angle of rotation of the image altering device 200 with respect to the objective 400 and uses this angle of rotation when transforming the digital image to compensate for the current pan and/or tilt angle. To perform such image transforming, i.e. to

rotate a digital image in one or more than one direction, is believed to be well within reach of a man skilled in the art of digital cameras. Therefore, the internal structure of the image transforming unit 800 will not be described herein.

The memory 700 may be implemented by any commercially available memory, such as an SRAM memory.

As indicated in FIG 1, the digital camera 300 may be connected to a network 900, such as an Ethernet or Token Ring network, which in turn may be part of the Internet. In such an application, the controller 600 of the digital camera 300 is provided with appropriate software for allowing the digital camera 300 to act as a web camera available on the network 900, i.e. a web server that produces digital images.

The pan and/or tilt angle of the digital camera 300, or more specifically the angle(s) by which the image altering device changes the field of view of the camera 300 with respect to a central axis of the objective 400, may be set and changed by a user of the camera by accessing the controller 600 through the network 900. Alternatively, the pan and/or tilt angle(s) may be controlled from a computer directly connected to the digital camera 300.

Referring now to FIGs 5 and 6, two simplified schematic drawings of the general mirror arrangement and mechanism for altering the image according to a preferred embodiment of the present invention is shown. The image producing apparatus comprises a camera housing 6 and an optical input 5, such as a generally known lens or objective, for producing a digital image representing an object located in the visual volume surrounding the image producing apparatus. The mirror arrangement of the image altering device is located on a base plate 8, externally mounted to the camera.

03630454-101100

The image altering device of the invention includes a rotatably mounted tilting mirror 1 and a driving device 7 for rotating the tilting mirror 1 according to a control signal. The driving device 7, in its simplest form, receives a control signal and in response to that either turns the tilting mirror 1 over to change the field of view or rotates the tilting mirror 1 to achieve a panning and/or tilting functionality. In the preferred embodiment, the tilting mirror 1 has a first plane surface 2 and a second curved surface 3. By putting the tilting mirror 1 in the position shown in FIG 5, the first plane surface 2 is inserted into the optical path 31 of the image producing apparatus, thereby providing the image producing apparatus with a first narrow field of view. This is due to the law of reflection, which terms and theory are well known to those skilled in the art and are thoroughly described in the literature, for instance in chapter 3.4 and 3.7 of "Introduction to Optics", by Frank L. Pedrotti, S.J. and Leno S. Pedrotti, Prentice Hall, Upper Saddle River, New Jersey 07458, ISBN 0-13-501545-6. The law of reflection states that the reflected ray remains within the plane of incidence, making equal angles with the normal at the reflection point, in our case, on the mirror surface 2. In a plane mirror, selecting another reflection point does not alter the normal; i.e. an image formed by reflection in a plane surface has got unity magnification.

A fixed mirror 4, mounted directly in front of the objective 5, turns the optical path 31 of the image producing apparatus 6, thereby making it possible to optically cover a volume in the direction of the optical center axis of the objective 5. In the absence of the fixed mirror 4, the rotary mounted tilting mirror 1 would have to be located in a position directly in

front of the objective 5 in order to be located in the optical path of the image producing apparatus. The tilting mirror 1 would then block a ray emerging from an object located in the direction of the optical center axis of the objective 5.

FIG 6 again shows the preferred embodiment, this time with the tilting mirror 1 turned over to achieve a wider field of view. Referring to the discussion above, due to the convex curvature of the mirror surface 3, the law of reflection states that rays of light originating from an object in the optical path of the image producing apparatus will, when they are reflected in a convex surface, diverge in such a way that the magnification of the system will be less than unity.

FIG 7 shows a simplified schematic drawing of a first alternative embodiment of the present invention. In this embodiment, the rotatably mounted tilting mirror 10 includes, in addition to the first plane surface 11 and the second curved surface 12, a third surface 13 with an optical characteristic different from the first plane surface 11 and/or the second curved surface 12. One conceivable function of this third surface could be to reduce certain spectral components of the reflected light, e.g. to act as a light balancing filter in an indoor environment or to attenuate colors outside the yellow spectral band (approx. 570 nm) to achieve a contrast enhancement. Another conceivable function of this third surface could be to reduce, without distortion, the amount of light reflected from a bright object, located in a highly illuminated environment; i.e. the third surface 13 will act as a gray filter and equally attenuate the spectral components of the reflected light. In this alternative embodiment, the fixed mirror 14, the objective 15, the camera housing 16, the driving device 17

and the base plate 18 are adapted to function according to the corresponding components in FIGs 5 and 6.

The image altering device 200 will now be described in more detail with reference to FIGs 2-4.

5 The following elements are shown in these drawings:

Qty	Ref. No.	Name
1	1	Tilting mirror
1	2	First plane surface
1	3	Second curved surface
1	4	Fixed mirror
1	5	Camera lens
1	6	Camera housing
1	7	Driving device
1	8	Base plate
2	9	Motor
1	10	Tilting mirror (alt. embodiment)
1	11	First plane surface (alt. embodiment)
1	12	Second curved surface (alt. embodiment)
1	13	Third surface (alt. embodiment)
1	14	Fixed mirror (alt. embodiment)

1	15	Camera lens (alt. embodiment)
1	16	Camera housing (alt. embodiment)
1	17	Driving device (alt. embodiment)
1	18	Base plate (alt. embodiment)
2	19	Optical sensor
1	20	Timing belt tightener
1	21	Timing belt tightener
1	22	Belt wheel
1	23	Belt wheel
1	24	Timing belt
1	25	Timing belt
1	26	Guiding wheel
1	27	Mirror wheel
2	28	Fixing part
1	29	Bevel gear
1	30	Tilt shaft

The image altering device 200 has a mirror
 system, comprising a first fixed mirror 4 and a second
 5 tilting mirror 1. As previously mentioned with refe-
 rence to FIGs 5 and 6, the tilting mirror 1 has a
 first plane surface 2 and a second curved surface 3.
 The fixed mirror 4 is mounted directly in front of the

objective 5 at an angle of 37° relative to the optical center axis of the camera 300. The fixed mirror 4 is mounted to a mirror wheel 27, which is rotatable around the objective and hence provides a field of view with
5 an angle of rotation of between 0° and 360° .

In the center of the field of view the tilting mirror 1 is mounted, so that the axis of rotation thereof is perpendicular to the optical center axis of the camera. The tilting mirror 1 is carried on the
10 mirror wheel 27, thereby causing the tilting mirror 1 to rotate around the objective 5 together with the fixed mirror 4. Thanks to the geometrical arrangement of the mirrors 4 and 1 with respect to the objective 5, it is possible to monitor a large volume in a short
15 time.

The tilting mirror 1 is journaled in the mirror wheel 27 between two fixing parts 28. Opposite to the mirror wheel 27 a slightly smaller guiding wheel 26 is concentrically mounted. A tilt shaft 30 is eccentrically mounted to the mirror wheel, so as to cause
20 the tilting mirror 1 to move. The guiding wheel 26 transmits its motion to the tilt shaft 30 and from the tilt shaft 30 through a bevel gear 29 to the mirror. The arrangement resembles a planetary gear, where the
25 guiding wheel 26 represents a sun pinion and the tilt shaft represents a planet pinion. The mirror wheel 27 acts as holder of the planet pinion.

When the mirror wheel 27 does not move, if the guiding wheel 26 is rotated, the tilt shaft 30 will
30 rotate around its own axis, wherein the tilting mirror 1 will be rotated around its axis of rotation. Hence, the tilting mirror 1 is rotated with respect to the mirror wheel 27, and the center axis of the field of view will be angled with respect to the optical center
35 of the camera. If the mirror wheel 27 and the guiding

09080101.101100

wheel 26 rotates at the same angular velocity, there will be no relative motion in the tilt shaft 30 and consequently no rotation of the mirror 1 around its axis of rotation. However, the mirror wheel 27 as
5 a whole will rotate with the fixed mirror 4 and the tilting mirror 1 at a constant angle to the optical center axis of the camera.

In other words, by rotating the mirror wheel 27 and the guiding wheel 26 synchronously, the field of
10 view may be rotated 360° for any given tilt angle. Then, if the wheels are rotated relative to each other, the angle of the tilting mirror 1 will change, and the field of view may be again be rotated 360° for a new tilt angle. In this way, a very large volume around
15 the camera may be covered, and images may be obtained for any given location within this large volume. Moreover, by rotating the guiding wheel 26 a certain amount in relation to the mirror wheel 27, the tilting mirror 1 will be turned over at 180° , thereby switching from
20 narrow field of view to wide field of view, or vice versa, as described with reference to FIGS 5 and 6.

The mirror wheel 27 and the guiding wheel 26 are driven by respective motors 9. Belt wheels 22, 23, timing belts 24, 25 and timing belt tighteners 20, 21
25 are provided, as shown in FIGS 2-4.

The inventive image altering device provides at least the following advantages:

- Low moment of inertia for rotating parts
- High pan/tilt adjustment speed, short time
30 between angular settings
- High setting accuracy
- Compact design
- Few structural components
- Low manufacturing cost
- 35 Flexible design

D01101-13168960

Simple pan/tilt control

Multiple fields of view

Filtering and/or other image altering possibilities

- 5 The present invention has been described above with reference to a preferred embodiment. However, other embodiments than the one disclosed herein are possible within the scope of the invention, as defined by the appended independent patent claims.

00000000-00000000

CLAIMS

1. An image altering device for an image
producing apparatus (300) with an optical input (5),
5 characterized by:

a mirror (1) having a first plane surface (2) .
and a second curved surface (3),

a driving device (7) coupled to the mirror (1)
and adapted to rotate the mirror (1) to a first posi-
10 tion, where the first plane surface (2) is inserted
into an optical path (31) of the image producing appara-
tus (6), the optical path being external to the optical
input (5), thereby providing a first field of view of
the image producing apparatus, the driving device (7)
15 also being adapted to rotate the mirror (1) to a second
position, where the second curved surface (3) is in-
serted into the optical path of the image producing
apparatus, thereby providing a second field of view
of the image producing apparatus.

20

2. A device according to claim 1, where the
curved surface (3) forms a portion of a sphere.

3. A device according to claim 1 or 2, where
25 the first plane surface (2) has an angular displacement
of 180 degrees with respect to the second curved sur-
face (3).

4. A device according to any of claims 1-3,
30 where the mirror (10) comprises a third surface (13)
with an optical characteristic different from the first
plane surface (11) or the second curved surface (12),
the driving device (17) being adapted to rotate the
mirror (10) to a third position, where the third sur-
35 face (13) is inserted into the optical path of the
image producing apparatus.

2000-07-05 E:\PUBLIC\DOC\F\3313073.doc NJ

5. A device according to claim 4, where the third surface (13) is plane.

6. A device according to claim 4 or 5, where
5 the third surface (13) attenuates certain spectral components of the reflected light.

7. A device according to claim 6, where the spectral components of the reflected light are uniform-
10 ly attenuated.

8. A device according to any preceding claim, where the driving device (7) is adapted to receive a control signal from a control unit (600) and to rotate
15 the mirror (1) to the first position or to the second position depending on a value of the control signal.

9. A device according to any preceding claim, where the driving device (7) comprises at least one
20 belt for rotating the mirror.

10. A device according to any preceding claim, where the driving device (7) comprises at least one gear wheel for rotating the mirror.

25 11. A method of providing a plurality of fields of view of an image producing apparatus, **characterized** by:

rotating a mirror (1) having a first plane surface (2) to a first position, where the first surface (2) is inserted into an optical path (31) of the image producing apparatus, thereby providing a first field of view, the optical path being external to the optical input, and

30

00604101-101100

rotating the mirror (1) to a second position, where a second curved surface (3) is inserted into the optical path of the image producing apparatus, thereby providing a second field of view of the image producing apparatus.

12. A method according to claim 11, where the mirror (1) is rotated by an angle of 180 degrees.

10 13. A method according to claim 11 or 12, where the mirror (10) comprises a third surface (13) with an optical characteristic different from the first plane surface (11) or the second curved surface (12), the third surface (13) being inserted into the optical path
15 of the image producing apparatus, thereby providing a third field of view of the image producing apparatus.

14. A digital camera (300) having panning and/or tilting functionality, comprising: a camera housing
20 (6) with an optical input (5), such as a lens or objective; an image capturing unit (500) for producing a digital image from light received through the optical input (5); and a controller (600), **characterized by:**

25 a mirror (1), mounted externally to the camera housing (6), having a first plane surface (2) and a second curved surface (3), and

a driving device (7) coupled to the mirror (1) and adapted to rotate the mirror (1) to a first position, where the first plane surface (2) is inserted
30 into an optical path (31) of the digital camera (300), the optical path being external to the optical input (5), thereby providing a first field of view of the digital camera, the driving device (7) also being adapted to rotate the mirror (1) to a second position,
35 where the second curved surface (3) is inserted into

09680181.101100

the optical path of the digital camera, thereby providing a second field of view of the digital camera.

15 15. A digital camera according to claim 14, where the curved surface (3) forms a portion of a sphere.

10 16. A digital camera according to claim 14 or 15, where the first plane surface (2) has an angular displacement of 180 degrees with respect to the second curved surface (3).

15 17. A digital camera according to any of claims 14-16, where the mirror (10) comprises a third surface (13) with an optical characteristic different from the first plane surface (11) or the second curved surface (12), the driving device (17) being adapted to rotate the mirror (10) to a third position, where the third surface (13) is inserted into the optical path of the
20 digital camera.

18. A digital camera according to claim 17, where the third surface (13) is plane.

25 19. A digital camera according to claim 17 or 18, where the third surface (13) attenuates certain spectral components of the reflected light.

30 20. A digital camera according to claim 19, where the spectral components of the reflected light are uniformly attenuated.

21. A digital camera according to any of claims 14-20, where the driving device (7) is adapted to
35 receive a control signal from a control unit and to rotate the mirror (1) to the first position or to the

second position depending on a value of the control signal.

22. A device according to any of claims 14-21,
5 where the driving device (7) comprises at least one belt for rotating the mirror.

23. A device according to any of claims 14-22,
where the driving device (7) comprises at least one
10 gear wheel for rotating the mirror.

00000001.101100

ABSTRACT

A digital camera has a plurality of fields of view combined with a panning and/or tilting functionality. The camera comprises: a camera housing (6) with an optical input (5), such as a lens or objective. The camera also has an image capturing unit for producing a digital image from light received through the optical input, a controller, a mirror (1) having a first plane surface (12) and a second curved surface (13), and a driving device (7) coupled to the mirror and adapted to rotate the mirror to a first position, where the first plane surface is inserted into an optical path (31) of the digital camera, thereby providing a first field of view of the digital camera. The driving device is also adapted to rotate the mirror to a second position, where the second curved surface is inserted into the optical path of the digital camera, thereby providing a second field of view of the digital camera.

20

To be published with FIG 5.

2025 RELEASE UNDER E.O. 14176




FIG 1








FIG 3



**FIG 5****FIG 6**




FIG 7

0469131-1010D

As a below-named inventor, I hereby declare that:

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **AN IMAGE ALTERING DEVICE FOR AN IMAGE PRODUCING APPARATUS** the specification of which,

- (Revised 3/29/99)

0970-896X(200601)24:1;1-D

(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)

And I hereby appoint Charles C. Cary, Reg. No. 36,764 and Robert H. Kelly, Reg. No. 33,922, all of the law firm of **CARY & KELLY, LLP**, 1875 Charleston Road, Mountain View, California, 94043, and all practitioners who are associated with this firm as my principal attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

CARY & KELLY, LLP
1875 Charleston Road
Mountain View CA, 94043

Charles C. Cary at telephone number (650) 533.4844

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Typewritten Full Name of
Sole or First Inventor: Stefan LUNDBERG Citizenship: SW

Inventor's signature: _____ **Date of Signature:** _____

Residence: (City) Lund (State/Country) Sweden

Post Office Address: Magistratsvagen 55, A205, 226 44 Lund, Sweden

Full Name of Second Joint Inventor (if any): _____ Citizenship: _____

Inventor's signature: _____ **Date of Signature:** _____

Residence: (City) _____ (State/Country) _____

Post Office Address: _____